


JEKLENE OBJEMKE ZA CEVI HIGH PERFORMANCE HOSE CLAMPS

TEHNIČNE SPECIFIKACIJE / TECHNICAL SPECIFICATION

Tip Type	Material Material	Standard Norm	Medij Medium	Nastavek za ključ Hexagon
HS	W1	DIN 3017	Različni / various	SW 7
HSE	W5 INOX	DIN 3017	Agresivni / aggressive	SW 7* (6mm) HSE12


HS

Jeklene objemke za cevi
High performance Hose clips, band
and lock steel W1 zinc plated



HSE

Nerjavne objemke za cevi
High performance Hose clips, band
and lock stainless steel W5



Tip Type	Razpon Range	Navor / Torque					
		Širina traku Band-width		Debelina traku Band-thickness			
		b	max. Nm	s	B	h	L
HS 12	8-12	9	2+0.5	0.7	14	11.5	20.5
HS 16	10-16	9	2+0.5	0.8	14	11.5	20.5
HS 20	12-22	9	3+0.5	0.8	14	11.5	24
HS 25	16-27	9	5+0.5	0.8	16	13	31
HS 32	20-32	12	5+0.5	0.8	16	13	31
HS 40	25-40	12	5+0.5	1.0	16	13	31
HS 45	30-45	12	5+0.5	1.0	16	13	31
HS 50	35-50	12	5+0.5	1.0	16	13	31
HS 60	40-60	12	5+0.5	1.0	16	13	31
HS 70	50-70	12	5+0.5	1.0	16	13	31
HS 80	60-80	12	5+0.5	1.0	16	13	31
HS 90	70-90	12	5+0.5	1.0	16	13	37
HS 100	80-100	12	5+0.5	1.0	16	13	37
HS 110	90-110	12	5+0.5	1.0	16	13	37
HS 120	100-120	12	5+0.5	1.0	16	13	37
HS 130	110-130	12	5+0.5	1.0	16	13	37
HS 140	120-140	12	5+0.5	1.0	16	13	37
HS 150	130-150	12	5+0.5	1.0	16	13	37
HS 160	140-160	12	5+0.5	1.0	16	13	37
HS 170	150-170	12	5+0.5	1.0	16	13	37
HS 180	160-180	12	5+0.5	1.0	16	13	37
HS 190	170-190	12	5+0.5	1.0	16	13	37
HS 200	180-200	12	5+0.5	1.0	16	13	37
HS 210	190-210	12	5+0.5	1.0	16	13	37
HS 220	200-220	12	5+0.5	1.0	16	13	37
HS 230	210-230	12	5+0.5	1.0	16	13	37
HS 240	220-240	12	5+0.5	1.0	16	13	37
HS 250	230-250	12	5+0.5	1.0	16	13	37
HS 260	240-260	12	5+0.5	1.0	16	13	37
HS 270	250-270	12	5+0.5	1.0	16	13	37
HS 280	260-280	12	5+0.5	1.0	16	13	37

Tip Type	Razpon Range	Navor / Torque					
		Širina traku Band-width		Debelina traku Band-thickness			
		b	max. Nm	s	B	h	L
HSE 12*	8-12	8	1.5	0.7	10.5	9.5	17
HSE 16	8-16	9	2+0.5	0.8	14	14.5	21
HSE 20	12-20	9	2+0.5	0.8	14	14.5	24
HSE 25	16-25	9	3+0.5	0.8	14	14.5	24
HSE 32	20-32	9	3+0.5	0.8	14	14.5	24
HSE 40	25-40	9	3+0.5	0.8	14	14.5	26
HSE 50	32-50	9	3+0.5	0.8	14	14.5	26
HSE 60	40-60	9	3+0.5	1.0	14	14.5	26
HSE 70	50-70	9	3+0.5	1.0	14	14.5	26
HSE 80	60-80	9	3+0.5	1.0	14	14.5	26
HSE 90	70-90	9	3+0.5	1.0	14	14.5	26
HSE 100	80-100	9	3+0.5	1.0	14	14.5	26