

**SPOJKE DN 7,2 TIP 26KB - ESE INOX**  
**COUPLINGS DN 7,2 TYPE 26KB - ESE INOX**



**Delovni tlak**  
**Working pressure**

PN=35 bar, maksimalni delovni statični pritisk z varnostnim faktorjem od 4 do 1  
 PN=35 bar, maximum static working pressure with safety factor of 4 to 1

**Delovna temperatura**  
**Working temperature**


-15°C +100°C (FKM)  
 Odvisno od medija.  
 Depending on the medium.

\*ostala tesnila (EPDM, FFKM) kot opcija za doplačilo / other seals upon surcharge

**Pretok / Flow capacity** 660 L/min

**Oznaka imena**  
**Name code**

**ESEG = gladek / flat**  
**ESER = narebren / knurled**



dejanska velikost  
 actual size

Spojka / Coupling	Standard / Standard (AISI 303)
Ohišje / Back body	AISI 303
Ohišje ventila / Valve body	AISI 303
Drsni obroč / Sleeve	AISI 303
Ventil / Valve	AISI 303
Vzmet in vskočni obroč / Spring and Locking ring	AISI 301
Zaporni zatič / Locking pins	AISI 301
Zaporne kroglice / Locking balls	AISI 316
Tesnila / Seals	FKM
Vtikač / Plug	Standard / Standard (AISI 303)
Vtikač / Plug	AISI 303


TL = dolžina navoja/thread length, SL = dolžina nastavka/stem length

**SPOJKE / COUPLINGS**

TIP-zunanji navoj TYPE-male thread	A (mm)	Hex SW	Hex1 SW1	L (mm)	TL (mm)	SL (mm)	D (mm)	B (mm)	G (mm)
KD 1/4 A TIP 26KB - ESEG SPOJKA AISI303	G1/4	22		41	9		27		
KD 1/4 A TIP 26KB - ESER SPOJKA AISI303	G1/4	22		41	9		27		
KD 3/8 A TIP 26KB - ESEG SPOJKA AISI303	G3/8	22		42	10		27		
KD 3/8 A TIP 26KB - ESER SPOJKA AISI303	G3/8	22		42	10		27		
KD 1/2 A TIP 26KB - ESEG SPOJKA AISI303	G1/2	24		44	12		27		
KD 1/2 A TIP 26KB - ESER SPOJKA AISI303	G1/2	24		44	12		27		




TIP-notranji navoj TYPE-female thread	A (mm)	Hex SW	Hex1 SW1	L (mm)	TL (mm)	SL (mm)	D (mm)	B (mm)	G (mm)
KD 1/4 I TIP 26KB - ESEG SPOJKA AISI303	G1/4	22		41.5	10.5		27		
KD 1/4 I TIP 26KB - ESER SPOJKA AISI303	G1/4	22		41.5	10.5		27		
KD 3/8 I TIP 26KB - ESEG SPOJKA AISI303	G3/8	22		41.5	10.5		27		
KD 3/8 I TIP 26KB - ESER SPOJKA AISI303	G3/8	22		41.5	10.5		27		
KD 1/2 I TIP 26KB - ESEG SPOJKA AISI303	G1/2	24		43	12		27		
KD 1/2 I TIP 26KB - ESER SPOJKA AISI303	G1/2	24		43	12		27		



SPOJKE ZA INDUSTRIJO IN OBRT / INDUSTRIAL COUPLINGS

TIP-natični priključek TYPE-hose barb	A (mm)	Hex SW	Hex1 SW1	L (mm)	TL (mm)	SL (mm)	D (mm)	B (mm)	G (mm)
KD P6 TIP 26KB - ESEG SPOJKA AISI303	6	22		56		25	27		
KD P6 TIP 26KB - ESER SPOJKA AISI303	6	22		56		25	27		
KD P8 TIP 26KB - ESEG SPOJKA AISI303	8	22		56		25	27		
KD P8 TIP 26KB - ESER SPOJKA AISI303	8	22		56		25	27		
KD P9 TIP 26KB - ESEG SPOJKA AISI303	9	22		56		25	27		
KD P9 TIP 26KB - ESER SPOJKA AISI303	9	22		56		25	27		
KD P10 TIP 26KB - ESEG SPOJKA AISI303	10	22		56		25	27		
KD P10 TIP 26KB - ESER SPOJKA AISI303	10	22		56		25	27		
KD P13 TIP 26KB - ESEG SPOJKA AISI303	13	22		56		25	27		
KD P13 TIP 26KB - ESER SPOJKA AISI303	13	22		56		25	27		



## VTIKAČI / PLUGS

TIP-zunanji navoj TYPE-male thread	A (mm)	Hex SW	Hex1 SW1	L (mm)	TL (mm)	SL (mm)	D (mm)	B (mm)	G (mm)
KS 1/4 A TIP 26SB - ESE VTIKAČ AISI303	G1/4	22		43	9				
KS 3/8 A TIP 26SB - ESE VTIKAČ AISI303	G3/8	22		45	10				
KS 1/2 A TIP 26SB - ESE VTIKAČ AISI303	G1/2	24		47	12				



TIP-notranji navoj TYPE-female thread	A (mm)	Hex SW	Hex1 SW1	L (mm)	TL (mm)	SL (mm)	D (mm)	B (mm)	G (mm)
KS 1/4 I TIP 26SB - ESE VTIKAČ AISI303	G1/4	22		44	10.5				
KS 3/8 I TIP 26SB - ESE VTIKAČ AISI303	G3/8	22		44	10.5				
KS 1/2 I TIP 26SB - ESE VTIKAČ AISI303	G1/2	24		45.5	12				



TIP-natični priključek TYPE-hose barb	A (mm)	Hex SW	Hex1 SW1	L (mm)	TL (mm)	SL (mm)	D (mm)	B (mm)	G (mm)
KS P6 TIP 26SB - ESE VTIKAČ AISI303	6	22		54		25			
KS P8 TIP 26SB - ESE VTIKAČ AISI303	8	22		54		25			
KS P9 TIP 26SB - ESE VTIKAČ AISI303	9	22		54		25			
KS P10 TIP 26SB - ESE VTIKAČ AISI303	10	22		54		25			
KS P13 TIP 26SB - ESE VTIKAČ AISI303	13	22		54		25			

