

SPOJKE DN 2,7 TIP 20KA - ESMCE INOX
COUPLINGS DN 2,7 TYPE 20KA - ESMCE INOX



Delovni tlak
Working pressure


PN=35 bar, maksimalni delovni statični pritisk z varnostnim faktorjem od 4 do 1
 PN=35 bar, maximum static working pressure with safety factor of 4 to 1

Delovna temperatura
Working temperature

-15°C +150°C (FKM) standard
 Odvisno od medija.
 Depending on the medium.

*ostala tesnila (EPDM, FFKM) kot opcija za doplačilo / other seals upon surcharge

Pretok / Flow capacity 165 L/min



dejanska velikost
 actual size

Spojka / Coupling	Standard / Standard (AISI 303)
Ohišje / Back body	AISI 303
Ohišje ventila / Valve body	AISI 303
Drсни obroč / Sleeve	AISI 303
Ventil / Valve	AISI 303
Vzmet in vskočni obroč / Spring and Locking ring	AISI 301
Zaporne kroglice / Locking balls	AISI 316
Tesnila / Seals	FKM
Vtikač / Plug	Standard / Standard (AISI 303)
Vtikač / Plug profile	AISI 303

TL = dolžina navoja/thread length, SL = dolžina nastavka/stem length

SPOJKE / COUPLINGS

TIP - zunanji navoj TYPE - male thread	A (mm)	Hex SW	Hex1 SW1	L (mm)	TL (mm)	SL (mm)	D (mm)	B (mm)	G (mm)
KD M5 A TIP 20KA - ESMCE SPOJKA AISI303	M5	9		26	5		10.5		
KD 1/8 A TIP 20KA - ESMCE SPOJKA AISI303	G1/8	11		28	7		10.5		



TIP-notranji navoj TYPE-female thread	A (mm)	Hex SW	Hex1 SW1	L (mm)	TL (mm)	SL (mm)	D (mm)	B (mm)	G (mm)
KD M5 I TIP 20KA - ESMCE SPOJKA AISI303	M5	9		25	5		10.5		
KD 1/8 I TIP 20KA - ESMCE SPOJKA AISI303	G1/8	12		28	7		10.5		



TIP-natični priključek TYPE-hose barb	A (mm)	Hex SW	Hex1 SW1	L (mm)	TL (mm)	SL (mm)	D (mm)	B (mm)	G (mm)
KD P3 TIP 20KA - ESMCE SPOJKA AISI303	3			34.5		13	10.5		
KD P4 TIP 20KA - ESMCE SPOJKA AISI303	4			34.5		13	10.5		
KD P5 TIP 20KA - ESMCE SPOJKA AISI303	5			34.5		13	10.5		




TIP-priključek z matico za cev TYPE-plastic hose connection	A (mm)	Hex SW	Hex1 SW1	L (mm)	TL (mm)	SL (mm)	D (mm)	B (mm)	G (mm)
KD 34 TIP 20KA - ESMCE SPOJKA AISI303	3x4	9		34			10.5		
KD 35 TIP 20KA - ESMCE SPOJKA AISI303	3x5	9		34			10.5		
KD 46 TIP 20KA - ESMCE SPOJKA AISI303	4x6	9		34			10.5		



SPOJKE ZA INDUSTRIJO IN OBRT / INDUSTRIAL COUPLINGS

TIP-panelna vgradnja z matico za cev TYPE-panel mount, plastic hose connection	A (mm)	Hex SW	Hex1 SW1	L (mm)	TL (mm)	SL (mm)	D (mm)	B (mm)	G (mm)
KD 34 TIP 20KA - ESMCE SPOJKA PREGRADNA AISI303	3x4	12	11	45	17		10.5		M7X0.5
KD 35 TIP 20KA - ESMCE SPOJKA PREGRADNA AISI303	3x5	12	11	45	17		10.5		M7X0.5
KD 46 TIP 20KA - ESMCE SPOJKA PREGRADNA AISI303	4x6	12	12	45	17		10.5		M8X0.5



TIP-panelna vgradnja z natičnim priključkom TYPE-panel mount, hose barb	A (mm)	Hex SW	Hex1 SW1	L (mm)	TL (mm)	SL (mm)	D (mm)	B (mm)	G (mm)
KD P3 TIP 20KA - ESMCE SPOJKA PREGRADNA AISI303	3	12	11	51	17		10.5		M7X0.5
KD P4 TIP 20KA - ESMCE SPOJKA PREGRADNA AISI303	4	12	11	51	17		10.5		M7X0.5
KD P5 TIP 20KA - ESMCE SPOJKA PREGRADNA AISI303	5	12	12	51	17		10.5		M8X0.5




VTIKAČI / PLUGS


TIP-zunanji navoj TYPE-male thread	A (mm)	Hex SW	Hex1 SW1	L (mm)	TL (mm)	SL (mm)	D (mm)	B (mm)	G (mm)
KS M5 A TIP 20SF - ESMCE VTIKAČ AISI303	M5	7		18	5				
KS 1/8 A TIP 20SF - ESMCE VTIKAČ AISI303	G1/8	11		20	7				



TIP-notranji navoj TYPE-female thread	A (mm)	Hex SW	Hex1 SW1	L (mm)	TL (mm)	SL (mm)	D (mm)	B (mm)	G (mm)
KS M5 I TIP 20SF - ESMCE VTIKAČ AISI303	M5	7		17	5				
KS 1/8 I TIP 20SF - ESMCE VTIKAČ AISI303	G1/8	12		19	7				




TIP-natični priključek TYPE-hose barb	A (mm)	Hex SW	Hex1 SW1	L (mm)	TL (mm)	SL (mm)	D (mm)	B (mm)	G (mm)
KS P3 TIP 20SF - ESMCE VTIKAČ AISI303	3	7		24	13				
KS P4 TIP 20SF - ESMCE VTIKAČ AISI303	4	7		24	13				
KS P5 TIP 20SF - ESMCE VTIKAČ AISI303	5	9		24	13				



TIP-priključek z matico za cev TYPE-plastic hose connection	A (mm)	Hex SW	Hex1 SW1	L (mm)	TL (mm)	SL (mm)	D (mm)	B (mm)	G (mm)
KS 34 TIP 20SF - ESMCE VTIKAČ AISI303	3x4	8		25					
KS 35 TIP 20SF - ESMCE VTIKAČ AISI303	3x5	8		25					
KS 46 TIP 20SF - ESMCE VTIKAČ AISI303	4x6	8		25					



TIP-priključek z matico za cev TYPE-panel mount, plastic hose connection	A (mm)	Hex SW	Hex1 SW1	L (mm)	TL (mm)	SL (mm)	D (mm)	B (mm)	G (mm)
KS 34 TIP 20SF - ESMCE VTIKAČ PREGRADNI AISI303	3x4	12	11	38	17				M7x0.5
KS 35 TIP 20SF - ESMCE VTIKAČ PREGRADNI AISI303	3x5	12	11	38	17				M7x0.5
KS 46 TIP 20SF - ESMCE VTIKAČ PREGRADNI AISI303	4x6	12	12	38	17				M8x0.5



TIP-panelna vgradnja z natičnim priključkom TYPE-panel mount, hose barb	A (mm)	Hex SW	Hex1 SW1	L (mm)	TL (mm)	SL (mm)	D (mm)	B (mm)	G (mm)
KS 3 TIP 20SF - ESMCE VTIKAČ PREGRADNI AISI303	3	12	11	45	17				M7x0.5
KS 4 TIP 20SF - ESMCE VTIKAČ PREGRADNI AISI303	4	12	11	45	17				M7x0.5
KS 5 TIP 20SF - ESMCE VTIKAČ PREGRADNI AISI303	5	12	12	45	17				M8x0.5

