

KAMLOK ALUMINIJASTE HITRE SPOJKE US-Mil. Standard (MIL-C-27487) / DIN EN 14-420-7

KAMLOK ALUMINIUM QUICK COUPLINGS US-Mil. Standard (MIL-C-27487) / DIN EN 14-420-7

TEHNIČNE SPECIFIKACIJE / TECHNICAL SPECIFICATION

Maks. delovni tlak Max. working pressure	Temperatura Temperature	Material Material	Medij Medium	Material ročke Handle material	Material tesnila Material seal	Navoj Threads
PN 16 bar	-10°C +60°C	Aluminij Aluminium	Običajni mediji Common fluids	Medenina Brass	NBR	ISO 228-1 DIN 2999

C-ALU Spojke z nastavkom za cev / Couplings with hose stem according to US-MIL-Norm



Tip Type	D (mm)	h (mm)	Nazivna velikost Ident. size	Nazivni premer Passage	DN
50-C-ALU	15	64	24	8	15
75-C-ALU	21.4	92.5	32.5	13	20
100-C-ALU	27.3	106	37.3	19.5	25
125-C-ALU	34	112	46	25.5	32
150-C-ALU	40.4	118	54	31.7	40
200-C-ALU	53	135	63.8	44	50
250-C-ALU	66.7	147	76.5	57	65
300-C-ALU	79.3	161	92.2	67.5	80
400-C-ALU	104.7	164.5	120.2	94	100

D-ALU Spojke z notranjim navojem po DIN EN 14 420-7 / Couplings with female thread DIN EN 14 420-7 form DF and thread sealing ring



Tip Type	G	h (mm)	Nazivna velikost Ident. size	Nazivni premer Passage	DN
50-D-ALU	1/2"	45.3	24	15	15
75-D-ALU	3/4"	46	32.5	17.5	20
100-D-ALU	1"	56	37.3	23	25
125-D-ALU	1 1/4"	63	46	31	32
150-D-ALU	1 1/2"	66	54	37	40
200-D-ALU	2"	76	63.8	42	50
250-D-ALU	2 1/2"	83	76.5	62	65
300-D-ALU	3"	87	92.2	75	80
400-D-ALU	4"	92.5	120.2	103	100

B-ALU Spojke z zunanjim navojem po DIN EN 14 420-7 / Couplings with male thread DIN EN 14 420-7 form BF



Tip Type	R	h (mm)	Nazivna velikost Ident. size	Nazivni premer Passage	DN
50-B-ALU	1/2"	46.8	24	12.8	15
75-B-ALU	3/4"	47.5	32.5	19.5	20
100-B-ALU	1"	56	37.3	25.5	25
125-B-ALU	1 1/4"	63	46	32	32
150-B-ALU	1 1/2"	66	54	40	40
200-B-ALU	2"	76	63.8	50	50
250-B-ALU	2 1/2"	83	76.5	62	65
300-B-ALU	3"	87	92.2	76	80
400-B-ALU	4"	94.5	120.2	99	100

DC-ALU Čepi po DIN EN 14 420-7 / Dust Caps EN 14 420-7 form DC



Tip Type	h (mm)	Nazivna velikost Ident. size	DN
50-DC-ALU	34.8	24	15
75-DC-ALU	36	32.5	20
100-DC-ALU	45	37.3	25
125-DC-ALU	51	46	32
150-DC-ALU	54.2	54	40
200-DC-ALU	63	63.8	50
250-DC-ALU	65	76.5	65
300-DC-ALU	64	92.2	80
400-DC-ALU	70	120.2	100

E-ALU Spojka z nastavkom za cev po US-MIL-Norm / Plugs with hose stem according to US-MIL-Norm



Tip Type	G	h (mm)	Nazivna velikost Ident. size	Nazivni premer Passage	DN
50-E-ALU	15.1	72	24	8	15
75-E-ALU	21.5	102	32.4	13	20
100-E-ALU	27.3	102	36.7	19.5	25
125-E-ALU	34	108	45.5	25.5	32
150-E-ALU	40.4	113	53.5	31.7	40
200-E-ALU	53	131	63	44	50
250-E-ALU	66.7	142	75.8	57	65
300-E-ALU	79.3	166	91.5	67.5	80
400-E-ALU	104.7	173.5	119.5	94	100

A-ALU Spojke z notranjim navojem po DIN EN 14 420-7 / Plugs with female thread DIN EN 14 420-7 form AF and thread sealing ring



Tip Type	G	h (mm)	Nazivna velikost Ident. size	Nazivni premer Passage	DN
50-A-ALU	1/2"	40	24	13	15
75-A-ALU	3/4"	40	32.4	21.2	20
100-A-ALU	1"	48	36.7	24	25
125-A-ALU	1 1/4"	54.6	45.5	28.5	32
150-A-ALU	1 1/2"	56	53.5	36.5	40
200-A-ALU	2"	63	63	46	50
250-A-ALU	2 1/2"	68.2	75.8	56.6	65
300-A-ALU	3"	69	91.5	73	80
400-A-ALU	4"	76.5	119.5	98	100

F-ALU Spojka z zunanjim navojem po DIN EN 14-420-7 / Plugs with male thread DIN EN 14 420-7



Tip Type	R	h (mm)	Nazivna velikost Ident. size	Nazivni premer Passage	DN
50-F-ALU	1/2"	55	24	13	15
75-F-ALU	3/4"	55	32.4	21.2	20
100-F-ALU	1"	66	36.7	24	25
125-F-ALU	1 1/4"	73.6	45.5	28.5	32
150-F-ALU	1 1/2"	76	53.5	36.5	40
200-F-ALU	2"	86.5	63	46	50
250-F-ALU	2 1/2"	96.5	75.8	56.6	65
300-F-ALU	3"	100	91.5	73	80
400-F-ALU	4"	112	119.5	98	100

DP-ALU Spojke po DIN EN 14 420-7 / Dust Plugs DIN EN 14 420-7 form DP



Tip Type	h (mm)	Nazivna velikost Ident. size	DN
50-DP-ALU	31	24	15
75-DP-ALU	32	32.4	20
100-DP-ALU	40	36.7	25
125-DP-ALU	45	45.5	32
150-DP-ALU	45	53.5	40
200-DP-ALU	52	63	50
250-DP-ALU	55	75.8	65
300-DP-ALU	58	91.5	80
400-DP-ALU	61	119.5	100