

KAMLOK MEDENINASTE HITRE SPOJKE US-Mil. Standard (MIL-C-27487) / DIN EN 14-420-7

KAMLOK BRASS QUICK COUPLINGS US-Mil. Standard (MIL-C-27487) / DIN EN 14-420-7

TEHNIČNE SPECIFIKACIJE / TECHNICAL SPECIFICATION

Maks. delovni tlak Max. working pressure	Temperatura Temperature	Material Material	Medij Medium	Material ročke Handle material	Material tesnila Material seal	Navoj Threads
PN 16 bar	-10°C +60°C	Medenina Brass	Običajni mediji Common fluids	Medenina Brass	NBR	ISO 228-1 DIN 2999

C-MS Spojke z nastavkom za cev / Couplings with hose stem according to US-MIL-Norm



Tip Type	D (mm)	h (mm)	Nazivna velikost Ident. size	Nazivni premer Passage	DN
50-C-MS	15	64	24.3	8	15
75-C-MS	21.4	82	32.5	15	20
100-C-MS	27.3	91.5	37.3	21.4	25
125-C-MS	34	98	46	27	32
150-C-MS	40.4	103	54	33.7	40
200-C-MS	53	117	63.8	45	50
250-C-MS	66.7	145	76.5	58.4	65
300-C-MS	79	151.5	92.2	69.5	80
400-C-MS	104.5	159	120.2	94	100

D-MS Spojke z notranjim navojem po DIN EN 14 420-7 / Couplings with female thread DIN EN 14 420-7 form DF and thread sealing ring



Tip Type	G	h (mm)	Nazivna velikost Ident. size	Nazivni premer Passage	DN
50-D-MS	1/2"	43	24.3	15	15
75-D-MS	3/4"	45	32.5	17.5	20
100-D-MS	1"	54	37.3	23	25
125-D-MS	1 1/4"	61	46	31	32
150-D-MS	1 1/2"	63	54	37	40
200-D-MS	2"	72	63.8	47	50
250-D-MS	2 1/2"	82.5	76.5	62	65
300-D-MS	3"	85.5	92.2	75	80
400-D-MS	4"	90	120.2	103	100

B-MS Spojke z zunanjim navojem po DIN EN 14 420-7 / Couplings with male thread DIN EN 14 420-7 form BF



Tip Type	R	h (mm)	Nazivna velikost Ident. size	Nazivni premer Passage	DN
50-B-MS	1/2"	45.8	24.3	12.8	15
75-B-MS	3/4"	45	32.5	19.5	20
100-B-MS	1"	55.5	37.3	25.4	25
125-B-MS	1 1/4"	62.5	46	34	32
150-B-MS	1 1/2"	65.5	54	40	40
200-B-MS	2"	71	63.8	50.5	50
250-B-MS	2 1/2"	83	76.5	63.5	65
300-B-MS	3"	84	92.2	76	80
400-B-MS	4"	92	120.2	100	100

DC-MS Čepi po DIN EN 14 420-7 / Dust Caps EN 14 420-7 form DC



Tip Type	h (mm)	Nazivna velikost Ident. size	DN
50-DC-MS	33	24.3	15
75-DC-MS	35.4	32.5	20
100-DC-MS	41.7	37.3	25
125-DC-MS	47.6	46	32
150-DC-MS	51	54	40
200-DC-MS	56.3	63.8	50
250-DC-MS	60.5	76.5	65
300-DC-MS	63.9	92.2	80
400-DC-MS	54.5	120.2	100

E-MS Spojka z nastavkom za cev po US-MIL-Norm / Plugs with hose stem according to US-MIL-Norm



Tip Type	D (mm)	h (mm)	Nazivna velikost Ident. size	Nazivni premer Passage	DN
50-E-MS	15.1	70	24	8.5	15
75-E-MS	21.5	86	32.4	15	20
100-E-MS	27.3	101	36.7	21.4	25
125-E-MS	34	106	45.5	27.3	32
150-E-MS	40.4	112	53.5	33.7	40
200-E-MS	53	128	63	46	50
250-E-MS	66.7	138	75.8	58.5	65
300-E-MS	79.3	160	91.5	69.5	80
400-E-MS	104.7	163	119.5	94	100

A-MS Spojke z notranjim navojem po DIN EN 14 420-7 / Plugs with female thread DIN EN 14 420-7 form AF and thread sealing ring



Tip Type	G	h (mm)	Nazivna velikost Ident. size	Nazivni premer Passage	DN
50-A-MS	1/2"	36.5	24	14.5	15
75-A-MS	3/4"	36.5	32.4	22.7	20
100-A-MS	1"	44.5	36.7	25.4	25
125-A-MS	1 1/4"	51	45.5	31	32
150-A-MS	1 1/2"	54	53.5	38.5	40
200-A-MS	2"	60.5	63	47.5	50
250-A-MS	2 1/2"	66	75.8	59	65
300-A-MS	3"	67	91.5	75	80
400-A-MS	4"	72	119.5	102.4	100

F-MS Spojka z zunanjim navojem po DIN EN 14-420-7 / Plugs with male thread DIN EN 14 420-7



Tip Type	R	h (mm)	Nazivna velikost Ident. size	Nazivni premer Passage	DN
50-F-MS	1/2"	51.4	24	14.5	15
75-F-MS	3/4"	51.5	32.4	22.7	20
100-F-MS	1"	62	36.7	25.4	25
125-F-MS	1 1/4"	70	45.5	31	32
150-F-MS	1 1/2"	73.5	53.5	38.5	40
200-F-MS	2"	82.5	63	42.5	50
250-F-MS	2 1/2"	94	75.8	59	65
300-F-MS	3"	97	91.5	75.3	80
400-F-MS	4"	110	119.5	102.4	100

DP-MS Spojke po DIN EN 14 420-7 / Dust Plugs DIN EN 14 420-7 form DP



Tip Type	h (mm)	Nazivna velikost Ident. size	DN
50-DP-MS	31	24	15
75-DP-MS	30.3	32.4	20
100-DP-MS	37.4	36.7	25
125-DP-MS	43	45.5	32
150-DP-MS	44.2	53.5	40
200-DP-MS	49.6	63	50
250-DP-MS	53.3	75.8	65
300-DP-MS	56.3	91.5	80
400-DP-MS	58	119.5	100