

NERJAVNE KLEŠČASTE SPOJKE DIN 3489 / DIN 3238


STAINLESS STEEL CLAW COUPLINGS DIN 3489 / DIN 3238

TEHNIČNE SPECIFIKACIJE / TECHNICAL SPECIFICATION


Maks. delovni tlak Max. working pressure	Temperatura Temperature	Material Material	Medij Medium	Razdalja med kleščami Claw distance	Material tesnila Material seal	Navoj Threads
PN 16 bar	-30°C +200°C	Inox 1.4401 / 1.4305 Stainless steel	Kemikalije Chemical medias	42mm	FKM	ISO 228



EKT-V
Spojke za cevi DIN 3489
Hose Claw Couplings DIN 3489



EKI-V
Spojke za cevi z notranjim navojem DIN 3489
Female Claw Couplings DIN 3489



EKA-V
Spojke za cevi z zunanjim navojem z zaščitno kapo DIN 3489
Male Claw Couplings DIN 3489 with thread protective cap

Tip Type	D (mm)	b (mm)	h (mm)	DN
EKT 10-V	10	63	65	6.5
EKT 13-V	13	63	65	9
EKT 19-V	19	63	65	15
EKT 25-V	25	63	65	20

Tip Type	G	b (mm)	h (mm)	DN
EKI 38-V	3/8"	63	41.5	15
EKI 12-V	1/2"	63	41.5	19
EKI 34-V	3/4"	63	41.5	20
EKI 10-V	1"	63	41.5	20

Tip Type	G	b (mm)	h (mm)	DN
EKA 38-V	3/8"	63	39	10
EKA 12-V	1/2"	63	39	14
EKA 34-V	3/4"	63	41,5	19
EKA 10-V	1"	63	41,5	20

Za tip cevi SLE
Hose assembly with hose type SLE



EKS-V
MODY varnostne spojke DIN 3238
MODY-Safety-Hose Claw couplings DIN 3238



EKTQ-V
Spojke za cevi z navojem (glede na DIN EN 14 424)
Hose Claw Couplings with thread ferrule (according to DIN EN 14 424)



EKSA-V
MODY varnostne spojke z zunanjim navojem DIN 3238
MODY-Safety Male thread Claw Couplings DIN 3238 with new gasket seat

Tip Type	D (mm)	b (mm)	h (mm)	DN
EKS 13-V	13	63	105	9
EKS 19-V	19	63	105	15
EKS 25-V	25	63	105	18

Tip Type	Cev Hose (mm)	b (mm)	h (mm)	DN
EKTQ 133-V	13x3	63	57	11
EKTQ 135-V	13x5	63	57	11
EKTQ 155-V	15x5	63	57	13
EKTQ 195-V	19x5	63	57	16
EKTQ 196-V	19x6	63	57	16
EKTQ 255-V	25x5	63	62	22
EKTQ 257-V	25x7	63	62	22

Tip Type	G	b (mm)	h (mm)	DN
EKSA 12-V	1/2"	63	77	13
EKSA 34-V	3/4"	63	80	18
EKSA 10-V	1"	63	82	18



EKS-KSM
MODY spojke z medeninastimi varnostnimi spojkami za paro
MODY-Safety-Hose Claw couplings with brass safety clamp for steam applications




EKSI-V
MODY spojke z notranjim navojem DIN 3238
MODY-Safety Female Thread Claw Couplings DIN 3238

Tip Type	Cev Hose (mm)	Mat. tesnila Mat. sealing	b (mm)	h (mm)	DN
EKS 13-KSM	13x6 (1/2)	TFEP (SDOR-N)	63	120	10
EKS 19-KSM	19x7 (3/4)	TFEP (SDOR-N)	63	120	15

Tip Type	G	b (mm)	h (mm)	DN
EKSI 12-V	1/2"	63	80	18
EKSI 34-V	3/4"	63	95	18
EKSI 10-V	1"	63	100	18

Čep za kleščaste spojke / Blank ends for claw couplings

Tip / Type	Izvedba / Execution	b (mm)	h (mm)	Material Material
EKO-V	brez verige / without chain	63	42	
EKM-V	z verigo / with chain	63	42	
EKMV-K	veriga (nadomestni del) / chain (spare part)	200		1.4301



Originalna tesnila / Original rubber ring DIN 3489

Tip / Type	Odpornost Resistance	Temp. Temp. (°C)	Material Material	Barva Colour	Trdota Shore A	Ø i	Ø a	h (mm)
GVOR	Kemikalije / Chem. medias	- 30 + 200	FKM	zelena green	50°	20	34	10.5
GDOR	Para / Steam	- 40 + 200	TFEP	rdeča red	65°	20	33	10
GPOR	Hrana / Foods	- 40 + 130	EPDM	nature	70°	20	34	10.5



Originalna tesnila za MODY / Original rubber ring for MODY-safety Claw couplings DIN 3238

Tip / Type	Izvedba Execution	Odpornost Resistance	Temp. Temp. (°C)	Material Material	Barva Colour	Trdota Shore A	Ø i	Ø a	h (mm)
SVOR-N	DIN 3238	Kemikalije Chem. medias	- 30 + 200	FKM	zelena green	70°	21	30	4
SVOR	OLD	Kemikalije Chem. medias	- 30 + 200	FKM	zelena green	60°	21	32,5	7
SDOR-N	DIN 3238	Para / Steam	- 40 + 200	TFEP	rdeča red	65°	21	30	4
SPOR-N	DIN 3238	Hrana / Foods	- 40 + 130	EPDM	natur	75°	21	30	4

